



NQuire 800 II / II Plus
tablets

Features

Integrated barcode scanner.

With built-in barcode scanners, look to the NQuire 800 II / II Plus as the perfect solution for your business. Work faster, more efficiently and more effectively.

Impact protection.

Rigorously designed and drop tested up to 1.2M, the NQuire 800 II / II Plus is protected from accidental bumps with reinforced edge and corner protection.

IP67 Certified.

For complete peace-of-mind, IP67 certification ensures that the device is dust proof and can be submerged into water up to 1 meter for 30 minutes.

Connectivity assured.

Always keep connected wherever your team is based with Bluetooth 4.0, a 3G micro-SIM card slot and Wi-Fi 802.11 ac/a/b/g/n connectivity. GPS tracking lets your team use location-based apps for increased accuracy and security wherever they are.

Easy-hold hand strap.

The NQuire 800 II / II Plus easy-hold hand strap has a fully removable back plate that securely screws into the tablets main body. With 360-degree rotation, users can position their tablet in either vertical or horizontal orientation for ease of use.

Built-in Stylus.

A discreet built-in capacitive stylus provides precision navigation and is designed to aid the function of any workforce.

Application Scenarios



NQuire 800 II / II Plus technical specifications

| | | |
|----------------|---------------------------------|---|
| Performance | Operating System | NQuire800 II: 32Bit Windows 10 Pro; NQuire800 II Plus: 64Bit Windows 10 Pro |
| | Processor | 1.44 GHz up to 1.92 GHz, 64-Bit Quad Core; Chip: Intel Atom® x5-Z8350 |
| | Memory RAM | NQuire 800 II: 2GB RAM; NQuire 800 II Plus: 4GB RAM |
| | Memory Flash | NQuire 800 II: 32GB ROM; NQuire 800 II Plus: 64GB ROM |
| | Memory Storage Expansion (Max.) | Up to 128GB (supports SDHC/SDXC cards) |
| Data capture | 1D | Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC / EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey |
| | 2D | PDF417, Data Matrix ECC200 / 000 / 050 / 080 / 100 / 140, QR Code |
| Physical | Dimensions (mm) | 235 * 147 * 22mm |
| | Weight | 875g |
| | Display | 8"800 x 1280 pixels, luminance: 380cd/m2(typical value), contrast ratio: 600:1(min), 800:1(typical) |
| | Keypad | 2x Capacitive shortcut keys (front bezel) |
| | Interfaces | Micro USB |
| | Battery Type | 8,000 mAh Lithium-polymer |
| | Expected Battery Life | 5-7 hours; 250 Hours Standby |
| | Power Supply Output | Gravity Acceleration Sensor (G-Sensor) |
| | Audio Jack | 3.5mm Audio jack |
| | Pogo Pin | √ |
| | Expansion Slot | up to 128GB (supports SDHC/SDXC cards) |
| | Camera | 5 MP with Autofocus |
| Environmental | Video | HD (1280 x 720) @ 30FPS |
| | Operating Temperature | -5°C to 40°C |
| | Storage Temperature | -20°C to 60°C |
| | Drop | 1.2m |
| Wireless | Sealing | IP67 |
| | WWAN Radio | 3G Micro SIM (3FF); Band 900 / 2100 MHz |
| | WLAN Radio | 802.11 ac/a/b/g/n, 2.4Ghz and 5Ghz, WEP, WPA2-Personal AES, WPA2-Enterprise AES, 8-2.11x WEP with EAP method PEAP, EAP-SIM, EAP-TTLS |
| | WPAN Radio | Bluetooth 4.0 |
| | GPS | GPS / GLONASS |
| Accessories | Standard | Stylus, hand strap, PSU, USB OTG cable |
| Certifications | Certifications | IEC2 / FDA II, IEC60825 / EN60825-1 |
| Warranty | Warranty | 2 years |